# INSTRUCTIONS

# **ARGUS BOLLARD**

#### 4639.06.30.52 4639.06.40.52

Please read the instructions before commencing installation and retain for future reference.

### **SPECIFICATIONS:**

- Fitting: Aluminum body with polycarbonate diffuser.
- Lamp types: 6W / LED 3000K and 4000K
- Protection against electric shock: CLASS I requires earth connection.
- Ingress Protection: IP 44. Protection against the entry of object greater than 1mm and water splashes.
- · Driver: Includes LED Driver
- Quality/Corrosive Rating: Suitable for outdoor domestic and commercial applications.
- Ambient temperature range: -20° to +40°

#### INSTALLATION INSTRUCTIONS:

A

Electrical products can cause death, injury or damage to property. Installation of this product must be carried out by a qualified electrician, in accordance with SANS 10142. On completion of installation, ensure that the

Certificate of Compliance is updated.



**CAUTION:** Risk of electric shock

**PLEASE NOTE:** The light source contained on this luminaire shall only be replaced by the manufacturer

or the service agent or a similar qualified person.

### Ensure mains supply is switched off.

- Mark and drill three holes according to the base where you would like to install the fitting. (Fig. 1)
- · Insert the plastic expansion screws.
- Pull out the terminal block mount from the fitting, remove the terminal block from it and connect to the mains supply (Fig. 2)

Brown (Live) - to Brown or Red Blue (Neutral) - to Blue or Black

Green/Yellow (Earth) - to Green/Yellow or Copper.

 Re-attach the terminal block to the mount and re-insert it into the fitting. Install the fitting on the ground with the screws provided (Fig. 3 and 4)

## Switch on mains supply

WARNING - Ensure all items and screws are secure.









