INSTRUCTIONS

FLIP READING LIGHT

246609.R.30 246609.R.31

Please read the instructions before commencing installation and retain for future reference.

SPECIFICATIONS:

- Fitting: Extruded aluminum body
- Lamp types: 10W / Gu10
- Protection against electric shock: CLASS I. Requires earth connection.
- Ingress Protection: IP20. Protection against the entry of solid bodies greater than 12mm
- Driver: Not Applicable
- Quality/Corrosive rating: Suitable for commercial and domestic indoor applications.
- Ambient temperature range: -8°C to +55°C.

INSTALLATION INSTRUCTIONS:

Electrical products can cause death, injury or damage to property. Installation of this product must be carried out by a qualified electrician, in accordance with SANS 10142. On completion of installation, ensure that the Certificate of Compliance is updated.



CAUTION: Risk of electric shock

Ensure mains supply is switched off.

- Remove the mounting bracket from the base and fix it to the ceiling, Rotate housing to remove it from the lamp holder. (Fig.1)
- Connect the fitting to its electrical source with the terminal block provided:
 - Brown (Live) to Brown or Red
 - Blue (Neutral) to Blue or Black
 - Green/Yellow (Earth) to Green/Yellow or Copper.(Fig. 2)
- Re-attach the base to the mounting bracket (Fig.3)
- Insert the Lamp and re-attach housing to the lamp holder: (Fig.4)

Switch main supply back on.

WARNING:

Ensure all items and screws are secure and fitted correctly.









