

INSTRUCTIONS

RATIONAL FOOTLIGHT ROUND AND SQUARE DOWNFACE

2379.01.30.31
2379.02.30.31

2379.01.40.31
2379.02.40.31



Please read the instructions before commencing installation and retain for future reference.

SPECIFICATIONS:

- **Fitting:** Body made in aluminium with tempered glass diffuser, lens and PVC housing.
- **Lamp types:**
1x2W Cool White 4000K 1x2W Warm White 3000K
- **Protection against electric shock:** CLASS III.
- **Ingress Protection:** IP54, protection against entry of dust, protection against water splashes
- **Ballast:** Includes LED driver.
- **Quality/Corrosive rating:** Suitable for indoor applications only.
- **Ambient temperature range:** -25°C to +55°C.

INSTALLATION INSTRUCTIONS:



Electrical products can cause death, injury, damage to property. Installation of this product must be carried out by a qualified electrician, in accordance with SANS 10142. On completion of installation, ensure that the Certificate of Compliance is updated.



CAUTION: Risk of electric shock.

PLEASE NOTE: The light source contained on this luminaire shall only be replaced by the manufacturer or the service agent or a similar qualified person.

Ensure mains supply is switched off.

- Make a cut out of 110*110mm. (Fig 1)
- Fit the mounting plate on to the 4x4 junction box which is fully recessed into the wall and plastered over. (Fig 2)
- Connect to the LED driver to the mains supply.(Fig 3)
Brown(Live) - to Brown or Red
Blue(Neural) - to Blue or Black
- **Skim over the mounting plate flush with the wall. (Fig. 4)**
- Connect the fitting to the LED driver. (Fig4)
- Place the fitting in the recessed box.(Fig 5)
- Switch on mains (Fig. 6)

WARNING:

- Ensure all items and screws are secure and fitted correctly.

RATIONAL FOOTLIGHT ROUND DOWNFACE RATIONAL FOOTLIGHT SQUARE DOWNFACE

Fig.1




Fig.2




Fig.3




Fig.4



Fig.5




Fig.6

