INSTRUCTIONS

2229 RND FIXED DOWNLIGHT

SPAZIOD

2229/30 2229/31 2229/32

Please read the instructions before commencing installation and retain for future reference.

SPECIFICATIONS:

- Fitting: Aluminum
- Lamp types: 10W / Gu10 / LED
- Protection against electric shock: Class II, does not require earth connection (as per specification)
- Ingress Protection: IP20. Protection against the entry of solid bodies greater than 12mm
- · Ballast: No driver required
- Quality/Corrosive rating: Suitable for domestic and commercial indoor use only.
- Ambient temperature range: -20°C to + 80°C

INSTALLATION INSTRUCTIONS:

Electrical products can cause death, injury, damage to property. Installation of this product must be carried out by a qualified electrician, in accordance with SANS 10142.

On completion of installation, ensure that the Certificate of Compliance is updated.



CAUTION: Risk of electric shock

Ensure mains supply is switched off.

- Make the relevant cut-out in the ceiling. (Fig. 1)
- Connect the driver to the main supply using the terminal block provided. (Fig. 2) Brown (Live) - to Brown or Red Blue (Neutral) - to Blue or Black
- Remove inner ring from the fitting (Fig. 3 & 4)
- Fit the lamp into lamp holder and fix the inner ring back into position.
- Inner ring can be replaced with directional insert accessories
- Insert the fitting into the ceiling ensuring that the mains lead is not trapped. Push the clips upward to snap firmly into position flush with the ceiling. (Fig. 5)

WARNING:

- Ensure all items and screws are secure and fitted correctly.
- Do not operate/install any product that appears damaged in any way.
- If damaged return the complete product to the place of purchase for inspection, repair or replacement.
- Ensure there are no components missing before commencing installation.

