



## SPD 1P pluggable 40kA ind.

SPN140D

### Architecture

Type of pole	1 P
--------------	-----

### Functions

Remote contact	no
----------------	----

### Controls and indicators

Indicator lamp	end of life indicator
----------------	-----------------------

### Main electrical features

Frequency	50/60 Hz
Nominal discharge current (In)	15 kA
Rated operational voltage Ue	230 V

### Voltage

Maximum continuous operating voltage Uc	275 V
Voltage protection level Up according to IEC61643-1	1,2 kV

### Electric current

Max discharge (Imax) or impulse (Iimp)	40 kA
--	-------

### Installation, mounting

Tightening torque	3,6Nm
Mounting type	din-Rail

### Connection

Connection cross-sect. rigid cable	35mm <sup>2</sup>
Connection capacity with rigid cable for earth	35 mm <sup>2</sup>
Connection cross-sect. flexible cable	25mm <sup>2</sup>
Connection capacity with flexible cable for earth	25 mm <sup>2</sup>

**Standards**

Test class IEC61643-1 / VDE0675-6	2/ C/ T2
European directive WEEE	concerned

**Safety**

Protection index IP	IP20
---------------------	------

**Use conditions**

Degree of pollution according to IEC 60664 / IEC 60947-2	2
Altitude	2000 m
Storage temperature	-40 to 80 °C