



COB Dotless Strip Light

10W | 230V

Applications:

Residential and Commercial Applications.


- Highly customizable with cutting points every 50mm.
- Genuine 3M adhesive backing tape for safe and quick installation.
- High CRI>80 ideal for specialized environments which require high colour rendering.
- 180° wide beam angle LED strip.
- Sanan SMD LED Chips with an efficacy of > 100lm/W.
- Increase the LED lifespan whilst reducing lumen decay by adding either our surface, recessed or corner pure aluminium profiles.
- Available in fully encased coated IP65.
- Available in either Warm White 3000K, Neutral White 4000K, Cool White 6000K, Red, Blue, Green, catering for all application requirements.
- Ideal for commercial/ residential applications.

Product Performance	
Wattage	10W
Colour Temperature & Stock Code	50m 6000K- XR410 50m 4000K- XR411 50m 3000K- XR12 1m 6000K- X410 1m 4000K- X411 1m 3000K- X412
Life Span/ LB Rating	25000hrs
IP Rating	IP65
Beam Angle	180°
Input Voltage	AC230V
Cutting Point	2.5 cm
Power Factor	>0.9
CRI	>80
Lumen Output	>1000lm/M
Lumen Efficiency	>100lm/W
LED Chips	COB
LED Chips Qty	286
Note	Max 50metre run with a power
Physical Characteristics	
Product Dimensions (mm)	10*4.5
Mounting Option	Double sided tape
Technical Parameters	
Input Current	0.043A
Regulatory Qualifications	
Class Rating	Class I
Energy Efficiency	А
Certification	CE, EMC

Packaging



Dimension Drawing



Accessories	
Optional accessories	XA030 - DYCE Quick Connector with wire XA031 - DYCE Strip to Strip Connector XA032 - DYCE L Connector XA033 - DYCE End CAP
Packaging info	
Carton Size (mm)	255*255*105
QTY/CTN	50
Net Weight	2,6
Gross Weight	2,8

DYCE STRIP LIGHT CONNECTOR ACCESSORIES



XA030DYCE Quick Connector with wire
L 216.5 x W 15.3 x H 8.5



XA031DYCE Strip to Strip
Connector
L 35.5 x W 15.3 x H 8.5



XA032 DYCE L Connector L 24 x W 24 x H 8.5



XA033DYCE End CAP
L 11 x W 12 x H 7

E&OE