




# Vista Mono Solar Post Top Light

25W





- A** Lock
- B** Turn on
- C** Motion mode (20% brightness or activate and deactivate motion sensor)
- D** Reduce brightness
- E** 3H/5H/8H Timer
- F** 10 Colour temperature (Smooth)
- G** Turn off
- H** CW/NW/WW
- I** Increase brightness
- J** Standard Mode
- K** RGB Flash
- L** 10 Colour temperature

Product Performance	
<b>Wattage</b>	25W
<b>Colour Temperature &amp; Stock Code</b>	• 3CCT (3000K/4000K/6000K) + RGB Motion Sensor - <b>FS100</b>
<b>Operating Temperature</b>	0~35°C
<b>IP Rating</b>	IP67
<b>Beam Angle</b>	110°
<b>Impact Protection Grade</b>	IK06
<b>Input Voltage</b>	4.5-6.5V
<b>CRI</b>	>70
<b>Lumen Output</b>	2 500 Lumens
<b>Lumen Efficiency</b>	100lm/W
<b>LED Chips</b>	2835
<b>LED Chips Qty</b>	180+180+30
<b>LED Chip Brand</b>	Sanan
<b>Dimmable</b>	Yes by remote
<b>Motion Sensor</b>	Yes (Optional via remote)
Physical Characteristics	
<b>Weight (kg)</b>	5.3 kg
<b>Housing Material</b>	Aluminum
<b>Product Dimensions (mm)</b>	φ485
<b>Mounting Option</b>	Aluminium Pole
<b>Bolts and Screws</b>	Stainless steel
Battery	
<b>Battery</b>	32700 Lithium LFP Battery
<b>Battery Specs</b>	3.2V 24 000Ah
<b>Battery Replaceable</b>	Yes
<b>Full Battery Operating Hours</b>	>14 hours

## Packaging



## Dimension Drawing



## Technical Parameters

<b>Input Current</b>	5A
<b>Output Voltage</b>	4.5-5V
<b>Humidity</b>	0~35°C
<b>Output Current</b>	4.8A
<b>TA &amp; TC</b>	90&85
<b>IES (Yes or No)</b>	No
<b>Regulatory Qualifications</b>	
<b>Class Rating</b>	Class III
<b>Energy Efficiency</b>	A
<b>Certification</b>	CE, EMC, MSDS, UN38.3
<b>Packaging info</b>	
<b>Storage Temp</b>	20~40°
<b>Carton Size (mm)</b>	52*29.5*52
<b>QTY/CTN</b>	2
<b>Solar Panel</b>	
<b>Wattage</b>	25W (21% efficiency Monocrystalline solar panel)
<b>Operating Temperature</b>	0~35°C
<b>IP Rating</b>	IP67
<b>Humidity</b>	0~35°C

E&OE